



worry-free & cost-effective.

No wiring required, reducing installation steps, and improving efficiency.

Solder-free quick-connect terminals for easy secondary processing. Solder-free terminals It can be cut to desired size and quickly installed with solder-free terminals. *High-voltage series of white and monochromatic light products support press-fit

Lightning resistance* Withstands 2kV Lightning surge.

It can withstand a 2kV lightning surge when used with an SPD lightning

protection module.

SPD lightning protection module

LIGHTNING RESISTANCE

ULTRA-HIGH STRUCTURAL STRENGTH Slight dim under close view, smooth light far view Ultra-high structural strength Special chips design, worry free about the dead-leds*. Parallel design of the smallest lighting unit, single LED failure does not affect normal illumination. Other chips are working normally

Single LED breakag

*Rotate the 1-meter neon strip 720° clockwise and 720° counterclockwise as 1 time test. After over 5,000 tests, the product still lights up normally

Unique structure design for more

uniform light distribution and

better visual effects.

High-intensity

UV test in 3000H.

Equivalent to 9 years of outdoor use, with slight color change.

*The neon strip still lights up when a single led is damaged, the damage is invisable

Innovative structure,

Twisting test: 5000 times* & Tensile Test ≥ 650N

Built in anti-tensile PC line

Trouble-free installation

Anti-twist high reliability.

LIGHTING EFFECT UPGRADED

Uniform light effect

Non-uniform light effect

New high-voltage neon RGB lighting. G/B/RGB modes suitable for expanded application scenarios

After UV 3000H test

Before UV 3000H test

OUTDOOR WEATHER RESISTANCE



AFS1224

Aluminum groove of reserved outlet position

Moldable groove

CREATING AN IDEAL LIGHTING SPACE FOR THE WORLD

Accessories

Flat mounting aluminum


Side mounting aluminum

groove

groove



ACS1224



WWW.COLORSLED.COM

TOP BEND

