

KING 2 Trimless Recessed

K2R40L2



E-mail:colors@colorsled.com

K2R40L2

Basic Parameters

Electrical Parameters

Optical Parameters

Version 1.00

7W	36V	0.15A	4000K	40°	250	≤19	570	66
----	-----	-------	-------	-----	-----	-----	-----	----

Note:

1. The above parameters are tested based on the light source with Color Rendering Index Ra90 and 3000K.
2. The input voltage and input current belong to the light source.
3. The brand of the light source is CITILED.
4. The power supply brand used includes EAGLERISE, BOKE and XIONGYUAN.
5. Assembling either honeycomb, Linear Spread Filter and Diffusion Filter will reduces luminous efficacy, UGR and beam angle.
6. luminous flux is allowed to have a ±10% tolerance.
7. The above parameters are typical values.

Light Distribution

Packing

Size (mm/box)	Quantity /box	QTY/CTN	N.WT (kg/box)	G.WT (kg/box)	G.WT (kg/ctn)	Size (mm/carton)
L156*W145*H95mm	1	48	0.25	0.26	12.48	L599*W485*H402mm

Attentions

- 1、 Non-professionals are prohibited from installing, disassembling and repairing the product.
- 2、 Avoid scratching, distortion and irregular bending of the product during installation; otherwise it may cause irreparable damage to the product.
- 3、 Please use professional cutting tools when cutting.
- 4、 Do not use any acid or alkaline adhesive to fix products.
- 5、 The product is only suitable for indoor dry places, can not be used in outdoor, seaside or wet environment.