

KING 2 Wall

K2W73L1



K2W73L1

Basic Parameters

Application	Indoor
Material	AL1070, Powder Coating
Coating	Black,White
IP Grade	IP65
Warranty	5 years
Working Temperature	-15°C~35°C


Electrical Parameters

Typ.power	12W
Control	Non-Dimming,Triac Dimming

Optical Parameters

LED	COB Light Source >50,000h-L80-B10 (Ta 25°C)
SDCM	<3 Step
CRI	>90
CCT	2700K,3000K,3500K,4000K
Beam Angle	36°

Dimensions



Luminaire Parameters

Type Power (W)	Input Voltage(LED) (V)	Input Current (mA)	CCT	Beam Angle	Luminaire Luminous Flux(lm)	UGR	Center Beam Candlepower (CBCP)	Beam Diameter
12W	36V	0.3A	2700K	36°	910	≤16	2100	63
12W	36V	0.3A	3000K	36°	960	≤16	2200	63
12W	36V	0.3A	3500K	36°	990	≤16	2250	63
12W	36V	0.3A	4000K	36°	1010	≤16	2300	63

Note:

1. The above parameters are tested based on the light source with Color Rendering Index Ra90 and 3000K.
2. The input voltage and input current belong to the light source.
3. The brand of the light source is CREE.
4. The brand of the power supply is LIFUD.
5. Incorporation of any of the following—honeycomb filter, Linear Spread Filter, or Diffusion Filter—will reduce luminous efficacy, UGR, and beam angle.
6. luminous flux is allowed to have a ±10% tolerance.
7. The above parameters are typical values.

Light Distribution

Packing

Size (mm/box)	Quantity /box	QTY/CTN	N.WT (kg/box)	G.WT (kg/box)	G.WT (kg/ctn)	Size (mm/carton)
L234*W132*H81mm	1	24	0.4	0.41	9.84	L483*W412*H346mm

Attentions

- 1、 Non-professionals are prohibited from installing, disassembling and repairing the product.
- 2、 Avoid scratching, distortion and irregular bending of the product during installation; otherwise it may cause irreparable damage to the product.
- 3、 Please use professional cutting tools when cutting.
- 4、 Do not use any acid or alkaline adhesive to fix products.
- 5、 The product can be used in outdoor or indoor.