

CSP-dot Series Specification



PD140

24V-10mm





【General description】

- 11m long strip driven by one end power supply
- The EFW process has a unique structure, using special profiles, does not require adhesive backing, and is easy to install.
- Side-exit cable plug, seamless lighting with no dark spots
- Life longer than 54000H, Ta: -40-60°C; Tc: 75°C (max)
- 5 years warranty



【Dimension】

Input voltage: DC24V	Max.length: 11000mm(36.1')
CRI: 90	Cutting unit: 50mm(1.97")
Max.power: 11W(1m)	LED pitch: 7.14mm(0.28")
Power range: 9-11W(1m)	Min. bend diameter: Φ 60mm(2.36")
Rated current: 0.42A(1m)	Mounting: 3M tape
Typical Power: 10W(1m)	Copper foil: 3oz
tape IP: IP20/IP67	
On-off times: 10000 (test times)	
Warranty: 5years	





【Photo-electric Parameters】




CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
Ra>90	SW	2700K	850	259	85	G
Ra>90	WW	3000K	850	259	85	G
Ra>90	NW	4000K	930	283	93	F
Ra>90	W	6500K	840	256	84	G

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/lmerter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.













[IP process information]



[Electronic & output data]


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO		No proof	10mm*1.7mm	2700K/3000K/4000K/6500K	100%
EFW		No proof	14mm*5.4mm	2700K/3000K/4000K/6500K	86%
EF		No proof	12mm*5mm	2700K/3000K/4000K/6500K	86%

[Product Solutions]

Name	Picture	Code	coding	description
Alumina carrier		/	CLS10EFW-12050100	size:L1000*W15.4*H7.4mm
Aluminum clip		/	FLS10EFW-1205	size:L25*W15.4*H7.4mm
2P male connector wire		/	AS-FC-0009(0.25M) AS-FC-0010(0.5M) AS-FC-0011(2M)	suitable for monochromatic led strip Wire lengths are optional:0.25M/0.5M/2M
2P female connector wire		/	AS-FC-0012(0.25M) AS-FC-0013(0.5M) AS-FC-0014(2M)	suitable for monochromatic led strip Wire lengths are optional:0.25M/0.5M/2M
2P T-Connection Wire		/	AS-FC-0027	Suitable for monochromatic led strip Wire length 150mm,IP67
Fixed Clip		94-02-00-0003	FSW10SA	Silicone clip, screw: PA 3*8mm, suitable for 10mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0046	DT10EA-A	Silicone plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0047	DW10EA-A	Silicone tail plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0025	CVT10EA-14100100	Transparent PVC mounting groove,suitable for 10mm FPC,silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel,suitable for ET/EF/EG waterproof LED strip
Monochrome remote		/	R6-1	output signal: RF Working voltage: 3VDC(CR2032) Remote control distance: 30m Working temperature:Ta:0-30 C ~0+55 C
Monotone light controller		/	CRI-GBA	Input voltage: DC12-48V Output current: 15A@12V/24V,10A@36V/48V Output Power: Max 180W@12V/Max 360W @24V/Max 360W@36V/Max 480W@48V Working temperature: -30 C ~ +55 C

【Packing】

Colors brand package(NONA)



General customized package(EF/EFW)



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	10000*10*1.7	10	300	0.12	12.5	13.5	41*41*26
EFW	10000*14*5.4	10	100	0.95	12.5	13.5	41*41*26
EF	10000*12*5	10	100	0.9	11.5	12.5	41*41*26

Remark: data with 10% tolerance

【Precautions】

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25C ~40 C. Storage temperature: 0 C ~60 C. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.