

Track System Specification

HIJ-30

— TLS-H series



【Basic Parameters】

- Material: Silicone Neon
- Coating: Black (RAL9005)
- IP grade: IP20
- CCT: 2700/3000/4000K optional
- CRI: 90
- SDCM(Light source): <3 Step (ANSI)
- Input voltage: AC220-240V
- Working temperature: -15℃~35℃
- Lighting direction: 360°
- Dimming method: Non-dimming

(Suitable for four-wire three-circuit guide rail)

/DALI dimming(Suitable for six-wire three-circuit guide rail)

optional

- Application: Indoor
- Certification: CE, ROHS, Reach
- Warranty: 5 years



【Luminaire Parameters】

Version	Model	Length	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	HIJ-30	/	220-240 VAC	/	7	7.5	>90	/	2700K	370
									3000K	390
									4000K	420

Note:

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

【Packing】

Model	Size (mm/box)	Quantity /box	Quantity /carton	NW (kg/box)	NW (kg/carton)	GW (kg/carton)	Size (mm/carton)
TLS-HIJ30-A930B7	755*68*48 [29.7"*2.7"*1.9"]	1	20	0.521	10.4	11.2	287*255*770 [11.3"*10"*30.3"]

【Attentions】

1. Non-professionals are prohibited from installing, disassembling and repairing the product.
2. Avoid scratching, distortion and irregular bending of the product during installation; otherwise it may cause irreparable damage to the product.
3. Please use professional cutting tools when cutting
4. Do not use any acid or alkaline adhesive to fix products
5. The product is only suitable for indoor dry places, can not be used in outdoor, seaside or wet environment.